











| Bewegungs-/Präsenzmelder<br>pirios  |  | 10.7.1            |    | 2017 Akkord         |                     |                      |              | Material          |                |                         |             |
|---|--|-------------------|----|---------------------|---------------------|----------------------|--------------|-------------------|----------------|-------------------------|-------------|
|   |  |                   |    | P<br>1.60<br>139.40 | K<br>1.21<br>101.30 | WS<br>1.00<br>107.-- | Zeit<br>Min. | Verkauf<br>1.1.17 | Eink<br>1.1.17 | Lieferant<br>Einh.-Nr.  |             |
| <b>i</b> Einregulierung IBS   |  |                   |    |                     |                     |                      |              |                   |                |                         |             |
| <b>Bewegungsmelder<br/>pirios 130°/180°</b>                                       |  |                   |    |                     |                     |                      |              |                   |                |                         |             |
|   |  |                   |    |                     |                     |                      |              |                   |                | Feller<br>Rab 27% 14.50 |             |
|    | AP-Bewegungsmelder pirios<br>180° 12m + 2x8m                         | 180 R • 535 220   | 10 | 294.85              | 210.40              | 190.--               | 38           | P                 | 194.05         | 121.29                  | 535 060 000 |
|   |  |                   | 20 | 302.50              | 215.05              | 195.--               | 41           | K                 | 146.75         |                         |             |
|    | NAP  | • 535 225         | 10 | 401.30              | 285.20              | 257.--               | 52           | P                 | 263.30         | 164.55                  | 535 265 000 |
|   |  |                   | 20 | 413.25              | 292.50              | 265.--               | 56           | K                 | 199.10         |                         |             |
|    | UP   | • 535 260         | 30 | 338.75              | 237.15              | 218.--               | 54           | P                 | 195.55         | 122.23                  | 535 261 000 |
|   |  |                   | 45 | 370.20              | 256.75              | 239.--               | 64           | K                 | 147.90         |                         |             |
|   |  |                   | 48 | 298.--              | 212.25              | 192.--               | 39           |                   |                |                         |             |
|   | Universaldimmer 420W<br>soft Ein Aus<br>Ausschaltvorwarnung Grundbel | DIM • 535 270     | 30 | 369.10              | 260.10              | 237.--               | 54           | P                 | 225.95         | 141.21                  | 535 308 000 |
|   |  |                   | 45 | 400.55              | 279.75              | 258.--               | 64           | K                 | 170.85         |                         |             |
|   |  |                   | 48 | 328.35              | 235.20              | 211.--               | 39           |                   |                |                         |             |
|   | SLA Slave  | • 535 261         | 30 | 290.20              | 202.95              | 187.--               | 48           | P                 | 164.05         | 102.52                  | 535 271 000 |
|   |  |                   | 45 | 321.65              | 222.60              | 208.--               | 58           | K                 | 124.05         |                         |             |
|   |  |                   | 48 | 249.45              | 178.05              | 161.--               | 33           |                   |                |                         |             |
|   | 12-48VDC Imp   | UNI • 535 262     | 30 | 378.60              | 265.80              | 243.--               | 57           | P                 | 225.95         | 141.21                  | 535 281 000 |
|   |  |                   | 45 | 410.--              | 285.40              | 264.--               | 67           | K                 | 170.85         |                         |             |
|   |  |                   | 48 | 337.85              | 240.90              | 217.--               | 43           |                   |                |                         |             |
|    | NUP  | 180 R • 535 263   | 30 | 406.30              | 288.10              | 260.--               | 54           | P                 | 262.05         | 163.77                  | 535 266 000 |
|   |  |                   | 45 | 437.75              | 307.75              | 281.--               | 64           | K                 | 198.15         |                         |             |
|   |  |                   | 48 | 365.55              | 263.25              | 234.--               | 40           |                   |                |                         |             |
|   | SLA Slave  | • 535 264         | 30 | 358.95              | 254.80              | 230.--               | 48           | P                 | 231.65         | 144.79                  | 535 276 000 |
|   |  |                   | 45 | 390.40              | 274.45              | 251.--               | 58           | K                 | 175.20         |                         |             |
|   |  |                   | 48 | 318.20              | 229.95              | 204.--               | 34           |                   |                |                         |             |
|  | 130° 10m + 2x8m Mh 2.5m  | 130 R • 535 259   | 30 | 377.10              | 266.05              | 242.--               | 54           | P                 | 232.85         | 145.52                  | 535 241 400 |
|   |  |                   | 40 | 377.40              | 266.25              | 242.--               | 54           | K                 | 176.10         |                         |             |
|   |  |                   | 45 | 408.55              | 285.65              | 263.--               | 64           |                   |                |                         |             |
|   |  |                   | 48 | 336.35              | 241.15              | 216.--               | 40           |                   |                |                         |             |
| <b>Bewegungsmelder<br/>pirios 360°</b>  |  |                   |    |                     |                     |                      |              |                   |                |                         |             |
|   |  |                   |    |                     |                     |                      |              |                   |                | Feller<br>Rab 27% 14.50 |             |
|  | UP-Bewegungsmelder pirios<br>360° Ø 14m Mh 2.5m                      | 360 R • 535 240   | 40 | 355.25              | 249.60              | 229.--               | 54           | P                 | 211.65         | 132.29                  | 535 233 000 |
|   |  |                   | 48 | 314.25              | 224.55              | 202.--               | 39           | K                 | 160.05         |                         |             |
|   | SLA Slave  | • 535 241         | 40 | 300.85              | 211.--              | 194.--               | 48           | P                 | 174.30         | 108.93                  | 535 234 000 |
|   |  |                   | 48 | 259.85              | 185.95              | 167.--               | 33           | K                 | 131.80         |                         |             |
|   | 12-48VDC Imp   | UNI • 535 265     | 40 | 403.25              | 284.45              | 259.--               | 57           | P                 | 250.20         | 156.38                  | 535 235 000 |
|   |  |                   | 48 | 362.25              | 259.35              | 232.--               | 43           | K                 | 189.20         |                         |             |
|  | NUP  | 360 R • 535 266   | 40 | 422.95              | 300.70              | 271.--               | 54           | P                 | 278.25         | 173.90                  | 535 212 000 |
|   |  |                   | 48 | 381.90              | 275.60              | 244.--               | 40           | K                 | 210.40         |                         |             |
| <b>Präsenzmelder<br/>pirios 360°</b>  |  |                   |    |                     |                     |                      |              |                   |                |                         |             |
|   |  |                   |    |                     |                     |                      |              |                   |                | Feller<br>Rab 27% 14.50 |             |
|  | UP-Präsenzmelder pirios<br>360° Ø 8m Mh 2.5m Imp                     | 360P 2R • 535 280 | 40 | 435.90              | 304.30              | 280.--               | 69           | P                 | 250.20         | 156.38                  | 535 237 000 |
|   |  |                   | 48 | 394.90              | 279.20              | 253.--               | 55           | K                 | 189.20         |                         |             |
|   | SLA Slave  | • 535 281         | 40 | 326.55              | 230.45              | 210.--               | 48           | P                 | 200.--         | 124.99                  | 535 236 000 |
|   |  |                   | 48 | 285.55              | 205.35              | 183.--               | 33           | K                 | 151.25         |                         |             |
|  | NUP  | 2R • 535 282      | 40 | 502.40              | 354.45              | 322.--               | 70           | P                 | 315.60         | 197.26                  | 535 217 000 |
|   |  |                   | 48 | 461.40              | 329.40              | 295.--               | 55           | K                 | 238.70         |                         |             |
| <b>Zubehör<br/>pirios 360°</b>  |  |                   |    |                     |                     |                      |              |                   |                |                         |             |
|   |  |                   |    |                     |                     |                      |              |                   |                | Feller<br>Rab 27% 14.10 |             |
|  | AP-Gehäuse pirios 360  | 535 242           | 10 | 28.10               | 19.60               | 18.--                | 4            | P                 | 17.25          | 10.77                   | 535 295 000 |
|   |  |                   | 20 | 35.75               | 24.30               | 23.--                | 7            | K                 | 13.05          |                         |             |

